

2003 AFCEE Technology Transfer Workshop

Promoting Readiness through Environmental Stewardship

Multi-Sensor Towed Array Detection System (MTADS)

James Montgomery AFCEE/ERS 27 February 2003









Multi-Sensor Towed Array Detection System (MTADS)

- Developed by US Naval Research Laboratory (NRL)
 - NRL POC Herb Nelson (202-767-3686)
 - Combined MTADS Airborne, Vehicular and Man-Portable Survey at the Badlands Bombing Range (BBR)
 Impact Area (Draft Report, January 03)
 - Funding
 - ESTCP The Environmental Security Technology Certification
 Program
 - AFCEE New Technology Funds



History of the Badlands Bombing Range

- Department of War annexed (1942) 341,725 acres of the Pine Ridge Reservation
 - Since 1960 lands been returning to Oglala Sioux Tribe
 - In 1978, all remaining BBR lands were returned except 2,486 acres termed the impact area
 - NRL in 1999 NRL conducts MTADS demonstration survey
 - 2002 AFCEE and Ellsworth Support Demonstration
 - Clear the Site as clear of UXO
 - Determine if Combined MTADS can be reliable and provide complete coverage of a site







- MTADS Technology Description
 - Vehicular Magnetometer System
 - Low-Magnetic-Signature Vehicle
 - Towed linear array of Magnetometer and Pulsed-Induction Sensors
 - Magnetometers are Cesium-Vapor full-field magnetometers



- MTADS Technology Description (continued)
 - Man-Portable Magnetometer System
 - Designed to collect data equivalent to the vehicular system
 - Constructed of fiberglass and plastic components with two wheels placed side by side between the sensors
 - Weight 38 lbs
 - Operator's backpack (GPS receiver, radio and battery) 18 lbs



MTADS Technology Description (continued)

- Airborne Magnetometer System
 - System mounted on Bell Helicopter Model 206L Series "LongRanger"
 - Magnetic Sensors Cs-Vapor (7)
 - Data Acquisition Computer mounted in the rear seat
 - Survey is monitored continually by operator in the rear seat
 - Helicopter Pilot flies the survey using onboard navigation display
 - Display provides left-right indicators
 - Altitude indicator
 - Real time data display so the operator can fly any missed areas



MTADS Results

- Survey Costs \$100/acre
- Remediation Costs \$200/target

Traditional Methods are:

- Labor-intensive
- Slow and inefficient
- Estimated seventy (70) percent of total budget of typical effort is spent on digging targets that do not turn out to be UXO

Production

- Man- Portable 2-3 acres/day
- Vehicular 15-25 acres/day, 6 mph
- Airborne up to 500 acres/day
- Detection Efficiency in excess of 95%

















Promoting Readiness through Environmental Stewardship























